

ಹಾಸನ ವಿಶ್ವವಿದ್ಯಾಲಯ

ಹೇಮಗಂಗೋತ್ರಿ ಹಾಸನ

HASSAN UNIVERSITY

HEMAGANGOTTHRI HASSAN -573226

Office of the Registrar

ಕುಲಸಚಿವರ ಕಾರ್ಯಾಲಯ


Email:reg.hassan.uni@gmail.com

ನಂ/ಹೆಚ್.ಯು.ಹೆಚ್/2023-24/792

ದಿನಾಂಕ : 06.03.2024

ಅಲ್ಪಾವಧಿ ಟೆಂಡರ್ ಆಹ್ವಾನ ಪ್ರಕಟಣೆ

ಕರಾಚೊವ ಮತ್ತು ಮಸೌಅನಿನಿ ಕರ್ನಾಟಕ ಪಾರದರ್ಶಕತೆ 2000 ಕಾಯ್ದೆ ಹಾಗೂ ಸ್ಟಾಂಡರ್ಡ್ ಟೆಂಡರ್ ದಾಖಲಾತಿ ಪ್ರಕಾರ ಕೆಳಕಂಡ ಕಾಮಗಾರಿಗಳಿಗೆ ಹಾಸನ ವಿಶ್ವವಿದ್ಯಾಲಯದ ಮಾನ್ಯ ಕುಲಪತಿಗಳು ಹಾಗೂ ಕುಲಸಚಿವರುಗಳ ಕಛೇರಿಗೆ ಅಲ್ಪಾವಧಿಯ ಪಾರ್ಲಿಮೆಂಟ್ ಕಾಮಗಾರಿ ಕೈಗೊಳ್ಳಲು ಅಲ್ಪಾವಧಿ ಟೆಂಡರ್ ಸಲ್ಲಿಸಲು ಕೊನೆಯ ದಿನಾಂಕ: 07 /03/2024 ರವರೆಗೆ ನಿಗದಿ ಪಡಿಸಲಾಗಿದೆ.ಸದರಿ ಟೆಂಡರ್‌ನಲ್ಲಿ ಸರಬರಾಜುದಾರರು ಭಾಗವಹಿಸಿ ತಮ್ಮ ಕನಿಷ್ಠ ಟೆಂಡರ್ ದರಗಳನ್ನು ಸಲ್ಲಿಸಬಹುದು ಹಾಗೂ ಇದರಲ್ಲಿ ಭಾಗವಹಿಸುವರು ರೂ 500/- ಶುಲ್ಕ ಪಾವತಿಸುವುದು ಹಾಗೂ ಟೆಂಡರ್ ತೆರೆಯುವ ದಿನಾಂಕ: 11 /03/2024 ಹೆಚ್ಚಿನ ಮಾಹಿತಿಗಳನ್ನು ಅಂತರಜಾಲದಲ್ಲಿ HUH.KARNATAKA.GOV.IN ನಲ್ಲಿ ಪಡೆಯ ಬಹುದು.

 06/3/24

ಕುಲಸಚಿವರು
ಹಾಸನ ವಿಶ್ವವಿದ್ಯಾಲಯ
ಹೇಮಗಂಗೋತ್ರಿ
ಹಾಸನ-573 226

Estimate for Providing aluminium partition at Office Room at Hassan University, Hassan

Particulars	No.	Dimensions			Contents	Unit
		L	B	D		
2	3	4	5	6	7	8
KSRB 7.14 : Providing, fabricating, assembling and fixing in position aluminium partitions using sections in combination of plain, single groove and double groove as per requirements for the frames of overall size 101.6mm x 44.45mm, 3.18mm.thick having section weight, plain sections 2.40kg/m single groove section 2.541kg/m. and double grovesection 2.683 kg/m and bottom 46 kg/m; aluminium louvres of size 77.6mmx27.6mm 1.7mm. thick section weight 0.483kg/m; bottom portions provided with 12mm. thick prelaminated sheet both side of approved colour lamination exterior grade; aluminium sections of mat finish or glossy finish using section, spacing of vertical member shall not exceed 0.6 m. c to c; sections are cut to the required lengths, joints mitered and corners grinded subdividing frames tenoned and rivetted to the frames, the assembled frame should be stiffened with corner angles stripped and fixed with screws, rawl plugs and teak wood gutties to R.C.C.columns or masonry on sides, R.C.C. lintels or beams at top and floor at bottom, including cutting chistling and making good with cement mortar to match the surface, providing and fixing bottom panel filled with the materials to a height of 0.9m. from floor level; and 5.5mm. thick plain glass for middle portion viz., 0.9m. to 2.13 m. and top panel with lower sections, the glass and panels fitted with glazing clips of 19mmx17.3mm. with thickness of 0.9mm. weight 0.124kg/m; aluminium sections pre-treated for removal of any rust and prevention of further rust formation, and coated with greasy materials for non-adherence of mortars or any other sticky materials; vertical members embedded in the flooring by making suitable size holes and fixing with cement mortar, with necessary opening for fixing of doors of standard size (excluding cost of door opening) All the frame should be throughly cleaned free from rust, scale or dirt including cost of materials, fixtures, labour and HOM of machinery	1	8.00	3.30	26.40		
	1	7.00	3.35	23.45		
	1	3.00	3.35	10.05		
	1	4.50	1.50	6.75		
				66.65		
Less Door portion			11.58			
			55.07			Sqm
2 KSRB 7.16 : Providing, fabricating, assembling and fixing in position aluminium shutters to the existing door frame in the partition using 47.62x44.45mm section thickness 3.18mm, weight 1.505kg/m for vertical frame; 47.62x44.45 thickness of 3mm, weight 1.42kg/m for top section, 49.91mmx44.45mm with wall thickness 3mm, weight 1.495kg/ m for central rail; and 114.3mmx44.45mm thickness 3.18mm, weight 2.646kg/m for bottom rail; aluminium sections and cut to length joint metred and corners grinded, the bottom rail and top rail hinged or pivoted, opening arrangements including providing and fixing standard approved accessories, such as aluminium handles, tower bolts, lock, pivots: hinges P.V.C. or rubber gasket, 12mm prelaminated sheets (Novopan) exterior grade of approved colour both sides same colour for bottom panel of maximum height 0.90m and 5.5mm thick plain glass for top panel (Novopan) and glass fixed with glazed clips 19mmx17.3mmx11mm, 0.9mm thick, weight 0.124kg/m; aluminium sections treated for removal of any rust and prevention of further rust formation, and coated with greasy materials for non-adherence of mortars or any other sticky materials, including cost of materials, fixtures, labour and HOM of machinery complete as per specifications. using aluminium section powdered coated to a minimum of 60-70 microns with exterior durable pure polyester grade powder of approved quality. [2018-19 SR P-38/7.16.2]	2	1.20	2.10	5.04		
	1	1.20	2.10	2.52		
	1	1.20	2.10	2.52		
	1	1.00	1.50	1.50		
				11.58		
						Sqm